Rules of **Department of Public Safety**

Division 40—Division of Fire Safety Chapter 2—Boiler and Pressure Vessel Safety Rules

Title		Page
11 CSR 40-2.010	Definitions	3
11 CSR 40-2.020	Administration	5
11 CSR 40-2.030	Existing Installation Power Boilers	17
11 CSR 40-2.040	Existing Heating Boilers	19
11 CSR 40-2.050	Existing Pressure Vessels	30
11 CSR 40-2.060	General Requirements	30

Title 11—DEPARTMENT OF PUBLIC SAFETY

Division 40—Division of Fire Safety Chapter 2—Boiler and Pressure Vessel Safety Rules

11 CSR 40-2.010 Definitions

PURPOSE: This rule formulates definitions concerning boilers and pressure vessels in Missouri.

Editor's Note: The following material is incorporated into this rule by reference:

1) American Society of Mechanical Engineers Code (ASME Code) (New York City: American Society of Mechanical Engineers, 1995).

In accordance with section 536.031(4), RSMo, the full text of material incorporated by reference will be made available to any interested person at the Office of the Secretary of State and the headquarters of the adopting state agency.

- (1) Act—The Boiler and Pressure Vessel Safety Act which was enacted as sections 650.200—650.290, RSMo.
- (2) ASME Code—The American Society of Mechanical Engineers (ASME) Boiler and Pressure Vessel Code as made, approved and adopted by the Council of the Society and approved and adopted by the board. Copies of the code may be obtained from the society at 345 E. 47th Street, New York, NY 10017.
- (3) Alteration—A change in any item described on the original Manufacturers' Data Report which affects the pressure capability of the boiler or pressure vessel. Nonphysical changes such as an increase in the maximum allowable working pressure (internal or external) or design temperature of a boiler or pressure vessel shall be considered an alteration. A reduction in minimum temperature such that additional mechanical tests are required shall also be considered an alteration
- (4) API-ASME Code—The American Petroleum Institute (API) in conjunction with the ASME Code as used in these rules shall mean the Code for Unfired Pressure Vessels for Petroleum Liquids and Gases.
- (5) Approved—Approved by the Board of Boiler and Pressure Vessel Rules.
- (6) Authorized inspection agency—One (1) of the following:

- (A) A department, division, or unit, established by a jurisdiction which has adopted and does administer one (1) or more sections of the ASME Code as a legal requirement and whose inspectors hold valid commissions issued by the National Board of Boiler and Pressure Vessel Inspectors (NB); and
- (B) An insurance company which has been licensed or registered by the appropriate authority of the state of Missouri to write and does write boiler and pressure vessel insurance and provides inspection service of boilers and pressure vessels in the state.
- (7) Board—The Board of Boiler and Pressure Vessel Rules created by the Act and empowered to make, alter, amend and interpret rules for the safe construction, installation, inspection, alteration and repair of boilers and pressure vessels.
- (8) Boiler—A pressurized vessel in which water is heated, steam is generated, steam is superheated, or any combination of these, under pressure or vacuum by the direct application of heat. The term boiler includes fired units for heating or vaporizing liquids other than water where these units are separate from processing systems and complete within themselves.
- (A) Power boiler—A boiler in which steam or other vapor is generated at a pressure of more than fifteen pounds per square inch (15 psi).
- (B) High temperature water boiler—A water boiler intended for operation at pressures in excess of one hundred sixty (160) psi and/or temperatures in excess of two hundred fifty degrees Fahrenheit (250°F).
- (C) Heating boiler—A steam or vapor boiler operating at pressures not exceeding fifteen (15) psi or a hot water boiler operating at pressures not exceeding one hundred sixty (160) psi or temperatures not exceeding two hundred fifty degrees Fahrenheit (250°F).
- (D) Electric boiler—A power boiler or heating boiler in which the source of heat is electricity.
- (E) Miniature boiler—A power boiler or high temperature water boiler which does not exceed the following limits:
- 1. Sixteen inches (16") inside diameter of shell;
- 2. Twenty (20) square feet heating surface (not applicable to electric boilers);
- 3. Five (5) cubic feet gross volume exclusive of casing and insulation; and
- 4. One hundred (100) psi maximum allowable working pressure.
- (F) Unfired steam boiler—An unfired pressure vessel or system of unfired pressure vessels intended for operation at a pressure in

excess of fifteen (15) psi steam for the purpose of producing and controlling an output of thermal energy.

- (G) Waste heat boiler—An unfired pressure vessels or system of unfired pressure vessels intended for operation in excess of fifteen (15) psi steam for the purpose of producing and controlling an output of thermal energy.
- (H) Heat recovery boiler—A vessel or system of vessels comprised of one (1) or more heat exchanger surfaces used for the recovery of waste heat.
- (I) Steam heating boiler—A steam boiler for operation at pressures not exceeding fifteen (15) psi.
- (J) Hot water heating boiler—A boiler in which no steam is generated, from which hot water is circulated for heating purposes and then returned to the boiler, and which operates at a pressure not exceeding one hundred sixty (160) psi and/or a temperature of two hundred fifty degrees Fahrenheit (250°F) at or near the boiler outlet.
- (K) Hot water supply boiler—A boiler completely filled with water that furnishes hot water to be used externally to itself at pressures not exceeding one hundred sixty (160) psi or at temperatures not exceeding two hundred fifty degrees Fahrenheit (250°F) at or near the boiler outlet.
- (L) Portable boiler—A boiler which is primarily intended for temporary location and the construction and usage permits it to be readily moved from one location to another.
- (M) Jacketed steam kettle/cooker—A gas or electrically fired kettle or cooker with jacket(s), operating at pressures not exceeding fifty (50) psi.
- (9) Certificate of competency—A certificate issued to a person who has passed the examination and met the experience requirements, prescribed by the board.
- (10) Certificate of inspection—A certificate issued by the chief inspector for the operation of a boiler or pressure vessel as required by the Act. The certificate of inspection shall be posted, under glass, at or near the object.
- (11) Certificate inspection—An inspection, the report of which is used by the chief inspector as justification for issuing, with-holding or revoking the inspection certificate. This certificate inspection shall be an internal inspection when required; otherwise, it shall be as complete an inspection as possible.
- (A) Internal inspection—As complete an examination as can reasonably be made of the internal, including water side, and external surfaces of a boiler or pressure vessel while it is shut down and manhole plates, handhold

plates or other inspection opening closures are removed as required by the inspector.

- (B) External inspection—An inspection made when a boiler or pressure vessel is in operation, if possible. An external inspection should include verification that required safety devices are operable, in good working order, and tested periodically.
- (12) Commission National Board—The commission issued by The National Board of Boiler and Pressure Vessel Inspectors to a holder of a certificate of competency who desires to make shop inspections or field inspections in accordance with the NB bylaws and whose employer submits the inspector's application to the NB for the commission.
- (13) Condemned boiler or pressure vessel—A boiler or pressure vessel that has been inspected and declared unsafe, or disqualified by legal requirements, by an inspector and a stamping or marking designating its condemnation has been applied by the chief or deputy boiler and pressure vessel inspector.
- (14) Director—The director of the inspection section of the Department of Public Safety.
- (15) Existing installation—Includes any boiler or pressure vessel constructed, installed, placed in operation or contracted on or before November 12, 1986.
- (16) Fittings and appliances—Include but are not limited to pressure relief devices, low water protection, pressure controls, temperature controls, thermometers, gages, expansion tanks, pipe fittings, pipe valves, pipe, etc., within the scope of these rules and the Act.
- (17) Inspector—The chief inspector, any deputy inspector, special inspector or owner-user inspector.
- (A) Chief inspector—The chief boiler and pressure vessel inspector appointed under the Act.
- (B) Deputy inspector—Any inspector appointed by the director under the provisions of the Act.
- (C) Special inspector—An inspector holding a Missouri certificate of competency and who is regularly employed by an insurance company authorized to insure against loss from explosion of boilers or pressure vessels in this state.
- (D) Owner-user inspector—An inspector who holds a valid National Board Owner-User Commission, who has passed the examination prescribed by the board and who is continuously employed as an inspector by an

owner-user inspection agency recognized by the state of Missouri.

- (18) Jurisdiction—A state, province, or territory of the United States, Canada, or Mexico or any city of the United States having a population of one (1) million or more that has adopted and does administer one (1) or more sections of the ASME Boiler and Pressure Vessel Code as a legal requirement, one (1) of which is Section I, and maintains a duly constituted department, bureau, division, or unit for the purpose of enforcement of the Code.
- (19) Lined potable water heater—A water heater with a corrosion resistant lining used to supply potable hot water.
- (20) National Board—The National Board of Boiler and Pressure Vessel Inspectors (NB), 1055 Crupper Avenue, Columbus, Ohio 43229, whose membership is composed of the chief inspectors of jurisdictions who are charged with the enforcement of the provisions of the ASME Code.
- (21) National Board Inspection Code—The manual for boiler and pressure vessel inspectors published by the NB from which copies may be obtained.
- (22) Nuclear power plant—One (1) or more nuclear power systems and containment systems.
- (23) Nuclear power systems—A system which serves the purpose of producing and controlling an output of thermal energy from nuclear fuel and those associated systems essential to the functions of the power system. The components of the system include items such as pressure vessels, piping systems, pumps, valves and storage tanks.
- (24) New boiler or pressure vessel installation—Includes all boilers or pressure vessels constructed, installed, placed in operation or contracted for after November 12, 1986.
- (25) Nonstandard boiler or pressure vessel—A boiler or pressure vessel that does not bear the ASME stamp, the API-ASME stamp or the stamp of any jurisdiction which has adopted a standard of construction equivalent to that required by the board.
- (26) Owner or user—Any person, firm or corporation legally responsible for the safe installation, operation and maintenance of any boiler or pressure vessel within the state of Missouri.

- (27) Owner-user inspection agency—An owner or user of pressure vessels who maintains a regularly established inspection department, whose organization and inspection procedures meet the requirements of the National Board rules and are acceptable to the board.
- (28) Pressure vessel—A vessel or an unfired steam boiler, as defined in subsection (8)(F); in which the pressure is obtained from an external source, by the application of heat from an indirect source or from a direct source other than those boilers defined in subsections (8)(A)—(M).
- (29) Psi-Pounds per square inch.
- (30) Reinstalled boiler or pressure vessel—A boiler or pressure vessel removed from its original setting and reinstalled at the same location or at a new location without change of ownership.
- (31) Repair—The work necessary to restore a boiler or pressure vessel to a safe and satisfactory operating condition, provided there is no deviation from the original design.
- (32) Second-hand boiler or pressure vessel— A boiler or pressure vessel which has changed both location and ownership since primary use.
- (33) Standard boiler or pressure vessel—A boiler or pressure vessel which bears the stamp of this state, the ASME stamp, the API-ASME stamp, both the ASME and NB stamp or the stamp of another jurisdiction which has adopted a standard of construction equivalent to that required by the board.
- (34) Water heater—A closed vessel in which water is heated by the combustion of fuels, electricity or any other source and withdrawn for use external to the system at pressures not exceeding one hundred sixty (160) psi and shall include all controls and devices necessary to prevent water temperatures from exceeding two hundred ten degrees Fahrenheit (210°F).

AUTHORITY: section 650.215, RSMo (1994).* Original rule filed May 12, 1986, effective Oct. 27, 1986. Amended: Filed Oct. 3, 1995, effective April 30, 1996.

*Original authority 1984, amended 1990, 1993, 1995.

11 CSR 40-2.020 Administration

PURPOSE: This rule addresses the safe construction, installation, inspection, operation, maintenance and repair of boilers and pressure vessels in Missouri.

Editor's Note: The following material is incorporated into this rule by reference:

- 1) American Society of Mechanical Engineers Code (ASME Code) (New York City: American Society of Mechanical Engineers, 1995);
- 2) National Board Inspection Code (Columbus, Ohio: National Board Inspection Code, 1995);
- 3) API-510 (Washington, D.C.: American Petroleum Institute).

In accordance with section 536.031(4), RSMo, the full text of material incorporated by reference will be made available to any interested person at the Office of the Secretary of State and the headquarters of the adopting state agency.

- (1) Minimum Construction Standards for Boilers and Pressure Vessels.
- (A) All new boilers, pressure vessels, water heaters and storage tanks, unless otherwise exempt, to be operated in this jurisdiction, shall be designed, constructed, inspected, stamped and installed in accordance with the American Society of Mechanical Engineers (ASME) Code and these regulations. Boilers and pressure vessels for which an ASME Manufacturer's Data Report is required shall bear the manufacturer's National Board (NB) number as registered with the National Board. A copy of the Manufacturer's Data Report, signed by the manufacturer's representative and the NBcommissioned inspector, shall be filed with the chief inspector through the National Board.
- (B) State Special. If a boiler or pressure vessel cannot bear the ASME and NB stamping or is to be constructed to another code approved by the board, details in the English language and United States customary units of the proposed construction material specifications and calculations shall be submitted to the chief inspector by the owner or user and approval as State Special obtained from the board before construction is started. Copies of all applicable codes and referenced standards shall be made available, as requested, by the board.
- (C) Before a second-hand boiler or pressure vessel is installed, application for permission to install it shall be filed by the

owner or user with the chief inspector and the chief inspector's approval obtained.

- (D) The following shall be exempt from the *ASME Code* construction requirements of subsection (1)(A):
- 1. Water heaters where none of the following limitations are exceeded:
- A. Heat input of two hundred thousand (200,000) British thermal units (BTU/hr) (57.1kw);
- B. Water temperature of two hundred ten degrees Fahrenheit ($210\,^{\circ}\text{F}$); and
- C. Nominal water capacity of one hundred twenty gallons (120 g) and which are provided with one (1) or more safety relief valves meeting the requirements of 11 CSR 40-2.040(6); and
- Coil-type hot water boilers used only for steam vapor cleaning of things such as machinery, equipment and building when none of the following limitations are exceeded:
- A. One inch (1") diameter tubing or three-fourths inch (3/4") nominal pipe size with no steam drums or headers attached;
- B. Nominal water containing capacity does not exceed six (6) gallons;
- C. Water temperature does not exceed three hundred fifty degrees Fahrenheit (350°F);
- D. Steam is not generated within the coil; and
- E. One (1) or more safety relief valves meeting the requirements of 11 CSR 40-2.030(6) must be installed and adequate controls are provided.
- (E) In any circumstances other than those previously mentioned, the owner or user shall contact the chief inspector.
- (2) Frequency of Inspections of Boilers and Pressure Vessels.
- (A) Power boilers; high pressure, high temperature water boilers; and waste heat boilers shall receive a certificate inspection annually which shall be an internal inspection where construction permits; otherwise it shall be as complete an inspection as possible. Boilers shall also be annually inspected externally while under normal operating conditions.
- (B) Unfired steam boilers shall receive a certificate inspection every year. The inspection shall be an external inspection and an internal inspection, where construction permits
- (C) Waste heat boilers shall receive a certificate inspection every year. The inspection shall be an internal inspection. Boilers shall also be annually inspected externally while under normal operating conditions.

- (D) Low pressure boilers, hot water heaters and hot water storage tanks shall receive a certificate inspection every two (2) years.
- 1. Steam or vapor boilers have an external inspection and an internal inspection every two (2) years, where construction permits.
- 2. Hot water heating and hot water supply boilers shall have an external inspection every two (2) years and, where construction permits, an internal inspection at the discretion of the inspector.
- 3. Water heaters including hot water storage tanks shall have an external inspection every two (2) years and shall include the function of all controls and devices.
- (E) Except as provided for in subsections (2)(F) and (G), pressure vessels subject to internal corrosion shall receive a certificate inspection every two (2) years. This inspection shall be internal, where construction permits and where preparation of the vessel for internal inspection does not present a hazard due to the materials involved. Pressure vessels not subject to internal corrosion shall be inspected externally every two (2) years.
- (F) Pressure vessels that are under the supervision of an owner-user inspection agency shall be inspected at the same interval unless otherwise agreed upon by the board with the agency.
- (G) Nuclear power plants, that are included in the Act, shall be inspected as provided by Section XI of the *ASME Code*.
- (H) Based upon documentation of actual service conditions by the owner or user of the operating equipment, the board, in its discretion, may permit variations in the inspection frequency requirements as provided in the Act.
- (3) Notification of Inspection. Certificate inspection, as required in section (2), shall be carried out prior to the expiration date of the certificate at a time mutually agreeable to the inspector and owner or user. External inspections may be performed by the inspector during reasonable hours and without prior notification. When, as a result of external inspection or determination by other objective means, it is the inspector's opinion that continued operation of the boiler or pressure vessel constitutes a menace to public safety, the inspector may request an internal inspection or an appropriate pressure test or both to evaluate conditions. In these instances the owner or user shall prepare the boiler or pressure vessel for the inspections or tests as the inspector designates.

- (4) Examination for an Inspector's Certificate of Competency.
- (A) Examination for an inspector's certificate of competency shall be held at the office of the board or at any other location to be selected by the board, four (4) times each year, namely the first Wednesday and one-half (1/2) day Thursday in the months of March, June, September and December. An applicant for an examination shall have education and experience equal to at least one (1) of the following:
- 1. A degree in mechanical engineering plus one (1) year of experience in design, construction, operation or inspection of high pressure boilers and pressure vessels;
- 2. A degree in a branch of engineering, other than mechanical engineering or an associate degree in mechanical technology plus two (2) years of experience in design, construction, operation or inspection of high pressure vessels; or
- 3. The equivalent of a high school education plus three (3) years of experience—
- A. In high pressure boiler and pressure vessel construction or repair;
- B. As an operating engineer in charge of high pressure boiler operation; or
- C. As an inspector of high pressure boilers and pressure vessels.
- (B) Applications for examination shall be in writing on a form to be furnished by the chief inspector stating the education of the applicant, a list of the applicants's employers, the applicant's period of employment and position held with each employer. Applications containing willful falsifications or untruthful statements shall be cause for rejection. Applications shall be submitted to the chief inspector at least forty-five (45) days prior to the date of examination. If the applicant's education and experience are acceptable to the board, the applicant shall be given a written examination dealing with the construction, maintenance and repair of boilers and pressure vessels and their appurtenances and the applicant shall be accepted or rejected on the merits of this examination. If the applicant is successful in meeting the requirements of the board, a certificate of competency will be issued by the chief inspector when the applicant is employed on a full-time basis by an authorized inspection agency as defined in 11 CSR 40-2.010(6) and (26). Upon the expiration of ninety (90) days, an applicant who failed to pass the examination will be permitted to take another written examination and the applicants's acceptance or rejection will be determined by the board on the basis of this examination.

- (5) Examination Fees. A fee as required in section (14) will be charged for each applicant (for each examination) taking the examination for a certificate of competency.
- (6) Certificate of Competency and Identification Card.
- (A) Upon the request of the applicant's employer, a certificate of competency and an identification card may be issued by the chief inspector to the following:
- 1. An inspector who is employed by the jurisdiction;
- 2. An inspector who is employed fulltime by an insurance company which is authorized to insure and does insure against loss from explosions of boilers and pressure vessels in the jurisdiction;
- 3. An inspector employed as described in either paragraph (6)(A)1. or 2. who conducts shop or field inspections of new boilers, pressure vessels or nuclear components in accordance with the applicable *ASME Code* requirements; or
- 4. An inspector who is continuously employed by a company which operates pressure vessels in this state and has a valid owner-user inspection agency agreement as provided for in section (11), provided that the applicant has satisfactorily passed the examination as set forth in section (4) or holds a valid commission or certificate of competency from a state that has a standard of examination substantially equal to that of this jurisdiction and a valid commission and a current commission card issued by the National Board.
- (B) The request for the certificate of competency and identification card shall be completed on forms to be provided by the chief inspector and shall be accompanied by, when applicable, a facsimile of the applicants's commission and commission card, certificate of competency and identification card as mentioned previously and a fee as required in section (14).
- (C) The certificate of competency and valid identification card shall be returned to the chief inspector when the inspector, to whom they were issued, is no longer employed by the organization employing the inspector at the time that the certificate was issued.
- (D) Each person holding a valid certificate of competency and who conducts inspections as provided by the Act shall apply to the chief inspector on forms provided and obtain a renewal identification card annually. A fee as required in section (14) for each card shall accompany each application.
- (E) An inspector's certificate of competency may be suspended by the chief inspector

- after due investigation and recommendation by the board for neglect of duty, incompetency, untrustworthiness or conflict of interest of the holder of the certificate, or for willful falsification of any matter or statement contained in the inspector's application or in a report of any inspection made by the inspector. Written notice of any suspension shall be given, within not more than ten (10) days, by the chief inspector, to the inspector and the inspector's employer. Persons whose certificates of competency have been suspended shall be entitled to an appeal to the board as provided for in the Act and to be present in person and represented by counsel at the hearing of the appeal.
- (7) Conflict of Interest. An inspector shall not engage in the sale of any services, article or device relating to boilers, pressure vessels or their appurtenances.
- (8) Inspection Reports to Be Submitted by Inspectors.
- (A) Inspectors, within one (1) year of the effective date of these rules (October 27, 1986) for boilers and three (3) years for pressure vessels, shall submit to the chief inspector an inspection report on forms acceptable to the board for each boiler and pressure vessel subject to inspection in this state. Forms NB-5, NB-6, NB-7 and the Missouri Boiler and Pressure Vessel-Report of Inspection are three (3) acceptable forms. Complete data shall be submitted on forms acceptable to the board for each nonstandard boiler or pressure vessel.
- (B) Subsequent inspections by deputy and special inspectors of both standard and non-standard boilers and pressure vessels shall be reported on forms acceptable to the board.
- (C) Inspection reports as required in subsections (8)(A) and (B) shall be submitted within thirty (30) days from the date of inspection.
- (D) Owner-user inspection agencies shall report in accordance with subsections (8)(B) and (C), or upon forms acceptable to the board, which shall be filed as provided in section (11).
- (9) Insurance Companies to Notify Chief Inspector of New, Cancelled or Suspended Insurance on Boilers or Pressure Vessels. All insurance companies shall notify the chief inspector, within thirty (30) days, of all boilers or pressure vessels on which insurance is written, cancelled, not renewed or suspended because of unsafe conditions.
- (10) Special Inspectors to Notify Chief of Unsafe Boilers and Pressure Vessels. If a special inspector, upon first inspection of a new

risk, finds that a boiler or pressure vessel, or any appurtenance of the boiler or pressure vessel, is in a condition that the inspector's company would refuse insurance, the company immediately shall notify the chief inspector and submit a report on the defects. If upon inspection a special inspector finds a boiler or pressure vessel to be unsafe for further operation, the inspector shall promptly notify the owner or user, stating what repairs or other corrective measures are required to bring the object into compliance with these rules. Unless the owner or user makes repairs or adopts other corrective measures promptly, the special inspector immediately shall notify the chief inspector. Until the corrections have been made, no further operation of the boiler or pressure vessel involved shall be permitted. If an inspection certificate for the object is required and is in force, it shall be suspended by the chief inspector. When reinspection establishes that the necessary repairs have been made or corrective actions have been taken and the boiler or pressure vessel is safe to operate, the chief inspector shall be notified. At that time an inspection certificate, where applicable, will be issued.

(11) Owner-User Inspection Agency.

- (A) Any person, firm, partnership or corporation operating pressure vessels in this jurisdiction may seek approval and registration as an owner-user inspection agency by filing an application with the chief inspector on prescribed forms and request approval by the board.
- (B) Application and registration shall show the name of the agency and its principal address in this state and the name and address of the person(s) having supervision over inspections made by the agency. Changes in supervisory personnel shall be reported to the chief inspector within thirty (30) days after the change.
- (C) Each owner-user inspection agency as required by the provisions of the Act and these regulations shall—
- 1. Conduct inspections of pressure vessels, not exempt by the Act, utilizing only qualified inspection personnel, as provided in section (6);
- 2. Retain on file at the location where the equipment is inspected, a true record or copy of each of the latest inspection reports signed by the inspector;
- 3. Execute and deliver to the chief inspector and those responsible for the operation of the pressure vessel, a true report of each inspection together with appropriate requirements or recommendations that result from the inspections;

- 4. Notify promptly the chief inspector of any pressure vessel which does not meet the requirements for safety;
- 5. Maintain inspection records which will include a list of each pressure vessel covered by the Act, showing a serial number and abbreviated descriptions as may be necessary for identification, the date of last inspection of each unit and approximate date for the next inspection, arrived at by applying the appropriate rules to all data available at the time the inspection record is compiled. Information regarding frequency and type of inspection is provided in section (2). The inspection record shall be readily available for examination by the chief inspector or his/her authorized representative during business hours; and
- 6. Submit to a periodic audit of the owner-user program and records, at least triennially. Fees will be in accordance with the rates established in subsection (14)(B).
- (12) Defective Conditions Disclosed at Time of External Inspection. If, upon external inspection, there is evidence of a leak or crack, sufficient covering of the boiler or pressure vessel shall be removed to permit the inspector to satisfactorily determine the safety of the boiler or pressure vessel. If the covering cannot be removed at that time, the inspector may order the operation of the boiler or pressure vessel stopped until such time as the covering can be removed and proper examination made.
- (13) Owner or User to Notify Chief Inspector of Accident. When an accident occurs to a boiler or pressure vessel, the owner or user promptly shall notify the chief inspector by submitting a detailed report of the accident. In the event of a personal injury or any explosion, notice shall be given immediately by telephone, telegraph or messenger, and neither the boiler or pressure vessel, nor any parts of the boiler or pressure vessel, shall be removed or disturbed before permission has been given by the chief inspector, except for the purpose of saving human life and limiting consequential damage.
- (14) Inspection Certificate, Inspection and Miscellaneous Fees.
- (A) If a boiler or pressure vessel after inspection, is found to be suitable and to conform to these regulations, the owner or user shall pay directly to the jurisdiction a fee of fifteen dollars (\$15) for each boiler and pressure vessel required to be inspected under the Act upon which an inspection certificate shall be issued. Checks and money orders for payment of all fees should be made payable to the Division of Fire Safety.

- (B) Inspection Fees. The owner or user of a boiler or pressure vessel required by the Act to be inspected by the chief inspector, or deputy inspector, shall pay when invoiced by the chief inspector, fees in accordance with the following schedule:
- 1. Power boilers and high pressure, high temperature water boilers.
 - A. Certificate internal inspections.
- (I) Boilers of fifty (50) square feet of heating surface or less \$26.
- (II) Boilers over fifty (50) square feet of heating surface and less than two thousand (2000) square feet of heating surface

\$47.

- (III) Boilers of two thousand (2000) square feet of heating surface or more, and less than four thousand (4000) square feet of heating surface \$54.
- (4000) square feet of heating surface or more, and less than ten thousand (10,000) square feet of heating surface \$64.
- (V) Boilers of ten thousand (10,000) square feet of heating surface or more \$80.
 - B. Certificate external inspections.
- (I) Boilers of fifty (50) square feet of heating surface or less \$20.
- (II) Boilers over fifty (50) square feet of heating surface \$29.
- C. Not more than the equivalent of the internal and external inspection fees shall be charged or collected for any and all inspections, as listed in paragraph (14)(B)1., of any boiler in any one (1) year except as provided in paragraph (14)(B)6.;
 - 2. Heating boilers.
 - A. Certificate inspections.
- (I) Heating boilers external inspection \$22.
- (II) Heating boilers internal inspection \$34.
- (III) Hot water supply boilers, water heaters, jacketed kettles \$18.
 - (IV) Storage water heaters \$16.
- B. Not more than one (1) fee shall be charged or collected for any and all inspections of any heating boiler or storage water heater, in any required inspection period except as provided in paragraph (14)(B)6.;
- 3. For boilers where the only source of heat is electrical energy, the fees of paragraphs (14)(B)1. and 2. shall apply based on one (1) kilowatt being equal to one (1) square foot of heating surface;
 - 4. Pressure vessels.
- A. Certificate inspections. Fees to be based on the maximum length of the vessel times the maximum width or diameter in feet.

- (I) Each pressure vessel subject to inspection having a product as determined above fifty (50) square feet or less \$15.
- (II) For each additional one hundred (100) square feet, or portions thereof, of area in excess of fifty (50) square

feet \$9.

- (III) Not more than forty-six dollars (\$46) shall be paid for each inspection on any one (1) vessel.
- (IV) A group of pressure vessels, such as the rolls of a paper machine or dryer operating as a single machine or unit, shall be considered as one (1) pressure vessel.
- (V) Not more than one (1) fee shall be charged or collected for any and all previously mentioned inspections of any pressure vessels in any required inspection period except as provided in paragraph (14)(B)6.;
- 5. Hydrostatic tests. When it is necessary to make a special trip to witness the application of a hydrostatic test, an additional fee based on the scale of fees applicable to a certificate inspection of the boiler or pressure vessel shall be charged; and
- 6. All other inspections, including shop inspections, special inspections and inspections of second-hand or used boilers or pressure vessels made by the chief or deputy inspector shall be charged for at the rate of not less than one hundred fifteen dollars (\$115) for one-half (1/2) day of four (4) hours or two hundred twelve dollars (\$212) for one (1) full day of eight (8) hours, including travel time, plus all expenses, including traveling, meals and lodging.
 - (C) Miscellaneous Fees.
- 1. Examination Fee for each examination \$21.
- 2. Commission Fee (including replacement or renewal) \$17.
 - 3. Commission Renewal Fee \$13.
- 4. Annual filing fees for owner-user inspection agencies based on the number of vessels.
- A. For statements covering not more than twenty-five (25) vessels (per vessel) \$2.
- B. For statements covering more than twenty-five (25) but not more than one hundred (100) vessels \$50.
- C. For statements covering more than one hundred (100) but not more than five hundred (500) vessels \$100.
- D. For statements covering more than five hundred (500) vessels \$200.
- (D) Disposition of Fees. The chief inspector shall account for and transfer all fees so received to the director of revenue.
- (E) If the owner or user of a boiler or pressure vessel which is required to be inspected refuses to allow an inspection to be made or refuses to pay the fee stipulated, a new

- inspection certificate shall not be issued. If a valid inspection certificate exists, it shall be suspended by the chief inspector until the owner or user complies with the requirements.
- (F) The owner or user who causes a boiler or pressure vessel to be operated without a valid certificate shall be subject to the penalty as provided for in the Act. It is the owner's responsibility to assure a valid certificate of inspection is posted at the location of the object.
- (15) Validity of Inspection Certificate. An inspection certificate, issued in accordance with section (14), shall be valid until expiration unless some defect or condition affecting the safety of the boiler or pressure vessel is disclosed provided, however, that a certificate issued for a boiler or pressure vessel inspected by a special inspector shall be valid only if the boiler or pressure vessel for which it was issued continues to be insured by a duly authorized insurance company.
- (16) Restamping Boilers and Pressure Vessels. When the stamping on a boiler or pressure vessel becomes indistinct, the inspector shall instruct the owner or user to have it restamped. Request for permission to restamp the boiler or pressure vessel shall be made to the chief inspector and proof of the original stamping shall accompany the request. The chief inspector may grant the authorization. Restamping shall be in accordance with the National Board Inspection Code. Notice of completion of the restamping shall be filed with the chief inspector by the inspector who witnessed the stamping on the boiler or pressure vessel, together with a facsimile of the stamping applied.
- (17) Penalty for Operation of Unsafe Boilers or Pressure Vessels.
- (A) If, upon inspection, a boiler or pressure vessel is found to be in a condition that it is unsafe to operate, the inspector shall notify the chief inspector and the inspection certificate may be suspended by the chief inspector.
- (B) Any person, firm, partnership or corporation causing the boiler or pressure vessel to continue to be operated shall be subject to the penalty provided in the Act.
- (18) Condemned Boilers and Pressure Vessels.
- (A) Any boiler or pressure vessel having been inspected and declared unfit for further service by an inspector shall be stamped by the chief inspector or a deputy inspector on either side of the state number with the letters XXX as shown by the following facsimile,

which will designate a condemned boiler or pressure vessel:

XXX MO XXX

This stamping shall be applied directly to the boiler or pressure vessel, whenever possible.

- (B) Any person, firm, partnership or corporation using, or offering for sale, a condemned boiler or pressure vessel for operation within this state shall be subject to the penalties provided by the Act.
- (19) Reinstallation of Boilers or Pressure Vessels. When a standard boiler or pressure vessel located in this jurisdiction is to be moved outside the jurisdiction for temporary use or repair, application shall be made by the owner or user to the chief inspector for permission to reinstall the boiler or pressure vessel in the jurisdiction. When a nonstandard boiler or pressure vessel is removed from this state, it shall not be reinstalled within this state.
- (20) Installation, Operation, Sale or Offering for Sale of Nonstandard Boilers or Pressure Vessels. The installation, operation, sale or the offering for sale of nonstandard boilers or pressure vessels in this jurisdiction is prohibited without permission from the board.
- (21) Installation of Used or Second-Hand Boilers or Pressure Vessels. Before a used or second-hand boiler or pressure vessel can be installed in this state, an inspection must be made by an inspector qualified by this jurisdiction. Data submitted by the inspector shall be filed by the owner or user of the boiler or pressure vessel with the chief inspector for approval. An internal and external certificate inspection of the object shall be made by an inspector qualified by this jurisdiction, prior to issuance of a certificate of inspection for the object. The inspection shall be documented on a form acceptable to the chief inspector. Boilers and pressure vessels, when installed in the jurisdiction, shall be equipped with fittings and appurtenances that comply with the regulations for new installations, in effect on the date of the installation. Exceptions must be referred to the chief inspector for resolution.
- (22) Reinstalled Boilers or Pressure Vessels. When a stationary boiler or pressure vessel is moved and reinstalled, the attached fittings and appurtenances shall comply with these regulations for new installations, in effect on the date of the installation. Exceptions must be referred to the chief inspector for resolution.

(23) Working Pressure for Existing Installations. Any inspector may decrease the working pressure on any existing installation if the condition of the boiler or pressure vessel warrants it. If the owner or user does not concur with the inspector's decision, the owner or user may appeal to the board which may request a joint inspection by the chief inspector or a deputy inspector and the inspector. The chief inspector shall render a report to the board and the board shall render the final decision, based upon the data contained in the inspector's reports.

(24) Repairs and Alterations.

- (A) When repairs or alterations are to be made to boilers and pressure vessels, permission shall be obtained from an inspector before the work is started. Organizations making repairs or alterations, must have one (1) of the following authorizations:
- 1. A valid certificate of authorization for use of the R symbol, issued by the National Board; or
- 2. A certificate of authorization from the board of boiler and pressure vessel rules.
- (B) All work shall conform to the rules of the *National Board Inspection Code* or API-510, as applicable.
- (25) Riveted Patches. In applying riveted patches, the design and method of installation shall meet the requirements of subsection (24)(B).

(26) Safety Appliances.

- (A) No person shall attempt to remove or do any work on any safety appliance prescribed by these regulations while the appliance prescribed is subject to pressure.
- (B) Should any of these appliances be removed for repair during an outage of a boiler or pressure vessel, they must be reinstalled and in proper working order before the object is again placed in service.
- (C) No person shall alter any safety or safety relief valves or pressure relief devices in any manner to maintain a working pressure in excess of that stated on the boiler or pressure vessel inspection certificate.
- (D) Repair of ASME- and NB-stamped safety or safety relief valves shall be made only by an organization which holds a valid Certificate of Authorization for use of the NB Safety or Safety Relief Valve Repair VR symbol stamp and the scope of the certificate includes the appropriate type of valve to be repaired.

(27) Requirements For New Installations.

(A) No boiler or pressure vessel shall be installed in this state after October 27, 1986, unless it has been constructed in accordance

with the ASME Code, registered with the NB and installed in conformity with these regulations except—

- 1. Those exempt by the Act; or
- 2. Those outlined in subsection (1)(B) of this rule.
- (B) The stamping shall not be concealed by lagging or paint and shall be exposed at all times unless a suitable record is kept of the location of the stamping so that it may be readily uncovered at any time this may be desired.

(28) Application of State Serial Numbers.

(A) Upon completion of the installation of a boiler or pressure vessel or at the time of the initial certificate inspection of an existing installation, each boiler or pressure vessel shall be stamped by the inspector with a serial number of the state, consisting of letters and figures to be not less than five-sixteenths inch (5/16") in height and arranged as follows:

MO 123456

Alternatively, a metal tag issued by the chief inspector, may be securely affixed using screws, rivets, wire or other means so that the tag cannot be easily removed. The "MO" number may not be transferred to any other object. The tag or stamping shall be placed as close to the ASME nameplate or stamping, as practicable.

(B) All cast iron, low pressure heating boilers (including all "HLW" stamped hot water supply boilers) shall have securely attached to the front of the boiler a corrosion-resistant metal tag of not less than one inch by four inches $(1" \times 4")$ in size which shall have the serial number of the state stamped on it. All pressure vessels constructed of cast iron, or of material of a thickness that it should not be stamped, shall have securely attached a corrosion-resistant metal tag not less than one inch by four inches $(1" \times 4")$ in size which shall have the serial number of the state stamped on it.

(29) Variations.

(A) Any person who believes the rules promulgated by the board are unreasonable or impose an undue burden upon the owner or user may request a variation from the rule. The request for variation shall be in writing and shall specify how equivalent safety is to be maintained. The board, after investigation and hearing as it may direct, may grant a variation from the terms of any rule provided special conditions as may be specified are maintained in order to provide equivalent safety.

- (B) When there is reason to believe, or upon receipt of a complaint that a variation does not provide freedom from danger equivalent to that described the published rule, the board, after notice to the owner or user and complainant after the hearing and investigation as it may direct, may continue in force, suspend, revoke or modify the conditions specified in any variation. No declaration, act or omission of the board or of the chief inspector, deputy inspectors or special inspectors other than a written order authorizing a variation as permitted previously, shall be deemed to exempt, either wholly or in part, expressly or implied, any owner or user from full compliance with the terms of
- (30) Penalties. Any person, firm or corporation violating any of the provisions of these rules shall be guilty of a misdemeanor and subject to a fine to be collected by suit or through compromise as provided for in section 650.270, RSMo of the Act. Each day of operation in violation of the provisions shall be considered a separate offense.

AUTHORITY: section 650.215, RSMo (1994).* Original rule filed May 12, 1986, effective Oct. 27, 1986. Amended: Filed Dec. 1, 1987, effective Feb. 11, 1988. Amended: Filed Sept. 27, 1990, effective Feb. 14, 1991. Amended: Filed Oct. 3, 1995, effective April 30, 1996.

*Original authority 1984, amended 1990, 1993, 1995.





MISSOURI DEPARTMENT OF PUBLIC SAFETY DIVISION OF FIRE SAFETY

BOILER OR PRESSURE VESSEL - REPORT OF INSPECTION

a attitue.								
DATE INSP	CERT EXP	DATE	CERT POST	STATE NO	NAT'L BRO NO)	OWNER NO	OTHER NO
NATURE OF BUSINESS			1		KIND OF INSP	1	CERT INSP	SPECIFIC LOC
					1		Y N	
OWNER ADDRESS								
				OWNED STATE			OWNER ZIO COOF	
OWNER CITY				OWNERSTATE			OWNER 2IP CODE	
USER								
USER ADDRESS								
USER CITY			<u>, , , , , , , , , , , , , , , , , , , </u>	USER STATE			USER ZIP CODE	COUNTY
TYPE BOILER	YR BLT	MANUFACTUR	RER	1			HEATING SURFACE	PRES GA TESTED
								Y N
USE			FUEL		METHOD OF F	IRE		
TYPE PRES VESSEL	YA BLT	MANUFACTUE	RER				VOLUME - CU. FT.	PRES GA TESTED
USE	<u> </u>		CORR SERVIC	CE .	CONTENTS		J	1 1
ALLOW PRES THIS INSP	ALLOW PR	ES PREV INSP	S R VALVE SE	TAT	HYDRO TEST		PSI	DATE
					Y	N		
EXPLAIN IF PRESSURE CHAN	IGED						SVRC REQUIRED	
				YES	NO		TOTAL SVRC	
UNLESS OTHERWISE	NOTED B	ELOW THE C	BJECT ON	THIS REPORT I	S CONSIDERED	SAFE	FOR CONTINUED S	ERVICE.
INSPECTOR'S FINDINGS	······································		-			······································		
NATURE OF BUSINESS NIND OF INSP EXT INT Y N OWNER ADDRESS OWNER ADDRESS OWNER CITY OWNER STATE OWNER ZIP CODE USER ADDRESS USER ADDRESS USER ADDRESS USER ADDRESS USER CITY USER STATE USER ZIP CODE COUNTY TYPE BOILER YR BLT MANUFACTURER FUEL METHOD OF FIRE TYPE PRES VESSEL YR BLT MANUFACTURER VOLUME · CU FT PRES GA TESTED Y N USE CORR SERVICE CONTENTS ALLOW PRES THIS INSP ALLOW PRES PREV INSP SR VALVE SET AT HYDRO TEST Y N SVAC REQUIRED IS CONDITION OF OBJECT SUCH THAT A CERTIFICATE MAY BE ISSUED IF NO, EXPLAIN FULLY BELOW. YES NO UNLESS OTHERWISE NOTED BELOW THE OBJECT ON THIS REPORT IS CONSIDERED SAFE FOR CONTINUED SERVICE.								
	TE MESP CERT EXP DATE CERT TOOT TUNE OF BUSINESS NER ACCORDS NER NER ACCORDS NO NER ACCORDS NER ACCORDS NO NER ACCORDS NER ACCORDS NO NER A							
INSPECTOR'S SIGNATURE							STATE COMMISSION N	UMBEH/EMPLOYED BY
FOR OFFICE USE O	NLY		SHOP INSPEC	CTION			TOTAL CHARGE	
INSPECTION			INSPECTION	CERTIFICATE			MISC EXPENSE	
SPECIAL INSPECTION			HYDROSTAT	IC INSPECTION			TRAVEL EXPENSE	
AO 812-0511 (9-89)		DISTRIBUT	TON: WHITE	E-STATE CAN	IARY/PINK - DISTR	UBUTIC:	N AS NEEDED	

10

FORM NB-4 NOTICE NEW BUSINESS OR DISCONTINUANCE USED BY AUTHORIZED INSURANCE INSPECTION AGENCIES

			JURISDICTION				_		1.	DATE OF NOTICE	
	Notice of:	000	New insurance business Discontinuance or cancellation Refusal to insure	3. Effective d	fato	4	. Type of	object	ΩL	ligh pressure boiler ow pressure boiler ressure vessel	
	OBJECT		6. OWNER'S NO.	7. JURISDICTION	NO. 8.	NATIONAL BOARD N	Ö.	9. N	VAME OF	MANUFACTURER	
	NAME OF OW	NER		·I			·				
-	NAME OF OW	NER IN	CLUDING COUNTY								
_	LOCATION OF	OBJEC	T INCLUDING COUNTY								
			T INCLUDING COUNTY SAME AS OWNER SHOW SAME	7							
	USER OF OBJ	ECT (IF	SAME AS OWNER SHOW SAME	15. CERTIFICATE IS		REASON FOR DISCO Phys. condition	NTINUANCI				
	USER OF OBJ	ECT (IF	SAME AS OWNER SHOW SAME	15. CERTIFICATE IS		REASON FOR DISCO					
	USER OF OBJ	ECT (IF	SAME AS OWNER SHOW SAME	15. CERTIFICATE IS		REASON FOR DISCO					

This form may be obtained from The National Board of Boller and Pressure Vessel Inspectors, 1055 Crupper Ave., Columbus, OH. 43229

Rev. 1

FORM NB-5 BOILER OR PRESSURE VESSEL DATA REPORT FIRST INTERNAL INSPECTION

Standard Form for Jurisdictions Operating Under the ASME Code

		DATE INSPECTED CERT EXP DATE CERTIFICATE POSTED DWNER NO.									JURISDICTION NUMBER NAT'L 90 NO. CO OTHER NO. CO									
1	1	DATE INSPECT	YEAR	MO MO	YEAR	1		OWNER NO			JURISOICTI	ON NO	UMBER			NAT'L BO NO	. 🔲 01	HER NO 🖂		
-	-		111			☐ Yes ☐	No		1_1_1			11	1_1_1	11	444		1 1 1	1_1_1	البنا	
		OWNER								- 1	NATURE OF	BUSI	RESS			KIND	OF INSPECTIO	ON CERTIFICAT		
- 1	2	1.1.1	1 1 1	1 1	1 1	1 1 1 1	1 1 3	1 1	1 1 1	1						□ in	t 🗆 Ext			
- 1	1	OWNER STREE	T ADDRESS			*·· *· *·					OWNERS C	ΙΤΥ					STATE	ZIP		
- 1		NUMBER	. 1 .															i	- 1	
╌	-	IISEDS NAME	ORIECTIO	CATION	1		-LL		لللل		SPECIFICAL		ON IN PLANT	<u> </u> _		1_1_	1 1 1 1			
-1	1	USERS NAME - OBJECT LOCATION USERS STREET ADORESS NUMBER								- (SPECIFIC D	UCAIR	ON IN PLANT	,			OBJECT FOO	ATION - COUNTY	- 1	
-	1										1.1:	1_1		11.	1 1 1	1 1 1	1 1 1	1 1 1 1	1	
- 1	٦[USERS CIT	Y			• • • • • • • • • • • • • • • • • • • •		STATE	ZIP	*	
- 1		TYPE FT WT CI Air Tank Water Tank Other								. 1							1			
┢	-								YEAR B	11117	MANUFACT	1950			111	حلحلت	YEAR INST		1	
ı	4								1000	UILI	MAITURACT	UNEK					TEAR INST	□New	1	
L									4 1 1	L	1 1	LL	1 1 1	lí	1 1 1	1 1 1	1 1	□Second	Hand	
1	_	USE POY	wer 🗆	Process		team Htg	☐ HWH	I DH	ws	1	FUEL (BOIL	ERI		METHO	O OF FIRING	(801LER)	PRESSURE	GAGE TESTED		
1	9	☐ Storage	☐ Heat	Exchang	e 🗆	Other											☐ Yes	□ No	- 1	
╌	+	PRESSURE						SAFETY - RI	FLIFF VALVI	FS	EXPLAIN IF	PRES	SURE CHANG	GED			1			
1	6		*****							-			obac branch						1	
L	_	This Inspe				spection		Set at		L										
-	7					ICATE MAY BE ISS								HYDRO					i	
L	1	Yes No (If no explain fully on back of form - listing code violations)												☐ Ye	s	,	osi Date		□ No	
ſ	٦	SHELL	DIAMETER	O ID	OVERALL	LENGIH		THICKNES	S	TOTAL	HTG SURFAC	E (80	HLERI			MATERIAL				
1	8	No.	in			ft.	in.		in.	1					Sq Ft	ASME Sp	ec Nos		- 1	
H	-	ALLOWABLE ST	TRESS	T2 TTUB	RAP		Cimala	HEADERS	- W T BOIL	ERS		TYPE				·				
1	9		nei	ı			Single	1							Wall C Ot	Other				
	4	psi Thks in. Double Thickness in. Box Sinuous Wtr Wall								mail Li U	11er									
1	o	TYPE LONGITU							- 1	RIVETED				PITCH				SEAM EFF	Ę	
₫ .	-	□ Lap	□ Butt		Welded	☐ Bra	zed	☐ Rive	Riveted Dia Hole in. in. X			in. X	X in. X in.			% 3				
Ĭ.		HEAD THICKN	ESS HEA	TYPE		☐ Fixed	□ M	ovable	ble RADIUS DISH ELLIP RATIO BOLTING											
ין <u>צ</u>	1		in. 🗆 F	lus [) Minu	s □ Flat	□ Qı	iick Oper	ning		in. No. Dia. in Material				3					
┇┠	+	TUBE SHEET T	HICKNESS	Tr	JBES					PITCH (W T BLRS)						LIGAMENT EFF				
i 1	2			- 1	۱o.	Dia.		in.	Length		ft			ir	1.		in. X in. %			
4 ي						R TUBES TO SHEL			2061											
3		FIRE				in.	Rear			1 6	AYED AREA Front Hea		Above Tu			- Rear Hea	ear Head Above Tubes			
Ž	Į	BOIL		Fron		111.				in, '		ι	Below Tu	ibes _			[Below	Tubes	2	
Complete when not registered National		STAYS ABOVE	TUBES				TYPE										AREA OF STAYS			
֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓	3	Front No.		Rear	No.		C) Head	to Head	1	□ Dia	gonal		□ Welde	ed	d □ Weldless Front			Rear	% % % % % % % % % % % % % % % % % % %	
į	П	STAYS BELOW	TUBES				TYPE				agonal Welded Weldless Fron				AREA OF STAYS					
Ė	- 1	Front No.		Rear	No.		☐ Head	to Head	1	□ Dia;				Front	Front Rear					
٦٢	1	FURNACE - TY	PE											TH TYPE LONG, SEAM			2			
11	4	Adamson (No. Sect.) 🗆 Co	rrugated 🗆 P	lain 🗆	Other				1		in.	ft.	•		iveted Sea	miess	
┢	-+	STAYBOLIS - I										-	DIAMETER		PITCH		NET ARE			
ŀ	5											- 1		1		. X	in.			
L			d [☐ Threaded ☐ Welded ☐ Hollow ☐ Drilled (Size															sq in.	
l,		SAFETY - RELIEF VALVES TOTAL CAPACITY									_ in.)			in.			111.			
	a			, viciace		CAPACITY				fm	OUTLETS			ın. j	PROPER	LY DRAINED				
I.	6	No.	EF VALVES Size	, werde			Hr					L	Size	ın. j	PROPER	LY DRAINED		on back of form)		
-	+	No.				CAPACITY		OTHER		fm tu/Hr	OUTLETS No.	LINES			PROPER	LY DRAINED				
-	7	No. STOP	Size		FOTAL	CAPACITY Lb/F		OTHER	CONNECT	fm tu/Hr ons	NO.		Size	DRAINED	PROPER	LY DRAINED				
-	+	No. STOP VALVES	Size ON STEAM	LINE DO	TOTAL	CAPACITY Lb/I ON RETURN LINI U Yes	ES No	□ Ye	CONNECT	fm tu/Hr ons	NO.	0	Size PROPERLY D No 111 "No	ORAINED	PROPER Yes	LY DRAINED	No" explain :	on back of formi		
1	+	No. STOP VALVES FEED PIPE	Size ON STEAM	A LINE No	FOTAL	CAPACITY Lb/I ON RETURN LINI U Yes	No TYPE	☐ YE	CONNECTI	fm tu/Hr ons No	NO.	CHE	Size PROPERLY O No 111 *No	PRAINED FEE	PROPER Yes n an back o	LY DRAINED No (11 *	No" explain :	on back of form)		
1	7	No. STOP VALVES FEED PIPE Size	Size ON STEAR	I LINE No	ED APPLI	CAPACITY LID/N ON RETURN LINI I Yes I ANCES	No TYPE	□ Ye	CONNECTI	fm tu/Hr ons No	OUTLETS No. STEAM I	CHE	Size PROPERLY D NO 111 "No" ECK VES	PRAINED	PROPER PR	LY DRAINED No (11 *	No" explain :	on back of formi		
1	7	NO. STOP VALVES FEED PIPE Size WATER GAGE OF	Size ON STEAT Yes	in. No	ED APPLI	CAPACITY LD/I ON RETURN LINI D Yes ANCES BLOW OFF PIPE	No TYPE	☐ Ye E DRIVE Steam	CONNECTI	fm tu/Hr ons No	OUTLETS No. STEAM I Yes	CHE VAL	Size PROPERLY D NO (11 "No ECK VES ENINGS COM	PLY WIT	PROPER PR	LY DRAINED I No (11 * I laim)	No" explain :	on back of form)		
1	7	No. STOP VALVES FEED PIPE Size	Size ON STEAT Yes	I LINE No	ED APPLI	CAPACITY LID/N ON RETURN LINI I Yes I ANCES	No TYPE	☐ Ye E DRIVE Steam	CONNECTI	fm tu/Hr ons No	OUTLETS No. STEAM I Yes	CHE VAL	Size PROPERLY D NO 111 "No" ECK VES	PLY WIT	PROPER PR	LY DRAINED I No (11 * I laim)	No" explain :	on back of form)		
1 1	8	NO. STOP VALVES FEED PIPE Size WATER GAGE OF	Size ON STEAM ON Yes	in. No	ED APPLI	CAPACITY Lb/H ON RETURN LINI D Yes D ANCES BLOW OFF PIPE	No TYPE	E DRIVE Steam	CONNECTI	fm tu/Hr ons No	OUTLETS NO. STEAM I Yes INSPECTIO	CHE VAL	Size PROPERLY D NO 111 "No ECK VES ENINGS COM O (11 "No" o	ORAINED * explai FEEI IPLY WITH	PROPER PR	LY DRAINED I No (11 * I Iaim) No	No" explain : RETURF ☐ Yes	on back of form)	E	
1	7	NO. STOP VALVES FEED PIPE Size WATER GAGE O	Size ON STEAN ON Yes CLASS	in. No	ED APPLI	CAPACITY Lb/H ON RETURN LINI D Yes D ANCES BLOW OFF PIPE	No TYPE	E DRIVE Steam	B CONNECTIONS	fm tu/Hr ons No	OUTLETS NO. STEAM I Yes INSPECTIO	CHE VAL	Size PROPERLY D NO 111 "No ECK VES ENINGS COM O (11 "No" o	ORAINEO * explai FEE D PLY WIT explain M, FEE	PROPER PROPER OF Yes H CODE OF BLOWOF	LY DRAINED I No (11 - 1 form) No form) F AND OTHE	No" explain : RETURF ☐ Yes	N LINE	E	
1	8	NO. STOP VALVES FEED PIPE Size WATER GAGE O NO. CAST IRON B Length	Size ON STEAM Yes SLASS IOILERS in.	I LINE No No In. No No. No.	ED APPLI	CAPACITY Lb/I ON RETURN LINI ON YES ON ANCES BLOW OFF PIPE Size in. Height	No TYPE	E DRIVE Steam cation in. No	B CONNECTIONS CTIONS B CONNECTIONS	fm tu/Hr ons No	OUTLETS NO. STEAM I Yes INSPECTIO Yes DOES WE Yes	CHE VAL ON OPE LDIN NO	Size PROPERLY D NO (11 "No" ECK VES ENINGS COM O (11 "No" a G OM STEAL	PLY WIT explain M, FEE explain	PROPER PR	LY DRAINED I No (11 - I Iaim) No aim) F AND OTHE	RETURN	N LINE NO NO NO NO NO NO NO NO NO	C	
1	8	NO. STOP VALVES FEED PIPE Size WATER GAGE O NO. CAST IRON B Length SHOW ALL CO	Size ON STEAM ON STEAM ON STEAM ON STEAM	I LINE No FE in. N TRY COCKS No. Width	ED APPLI	CAPACITY Lb/I ON RETURN LINI ON RETURN LINI ON YES ON ANCES BLOW OFF PIPE Size in. Height FORM. Give of	in. Loc	E DRIVE Steam cation in. No	B CONNECTIONS CTIONS CTIONS CH) for	fm tu/Hr ons No	OUTLETS NO. STEAM I Yes INSPECTIO Yes DOES WE DOES ALI	CHE VAL'	Size PROPERLY D NO 111 "No ECK VES ENINGS COM G ON STEAL O (11 "No" 4 TERIAL OTH	PRAINED * explain FEE	PROPER PROPER In an back of D LINE Yes On back of D, BLOWOF on back of AN AS INDI	LY DRAINED I No (11 - I Iaim) No orm) F AND OTHE orm) CATED ABOV	RETURN	N LINE NO NO NO NO NO NO NO NO NO	E.	
1	8	No. STOP VALVES FEED PIPE Size WATER GAGE O NO. CAST IRON B Length SHOW ALL C special obj	Size ON STEAM ON STEA	I LINE No In. No IRY COCKS No. Width ING ON 8	ED APPUI	CAPACITY Lb/f ON RETURN LINI Yes ANCES BLOW OFF PIPE Size in. Height FORM. Give consults as Do	in. Loo	E DRIVE Steam cation in. SEC	B CONNECTIONS CTIONS CTIONS CH) for	fm tu/Hr ons No	OUTLETS NO. STEAM I Yes INSPECTIO Yes DOES WE DOES ALI	CHE VAL'	Size PROPERLY D NO (11 "No" ECK VES ENINGS COM O (11 "No" a G OM STEAL	PRAINED * explain FEE	PROPER PROPER In an back of D LINE Yes On back of D, BLOWOF on back of AN AS INDI	LY DRAINED I No (11 - I Iaim) No orm) F AND OTHE orm) CATED ABOV	RETURN	N LINE NO NO NO NO NO NO NO NO NO	i E	
1 1 2 2 2	8	No. STOP VALVES FEED PIPE Size WATER GAGE O NO. CAST IRON B Length SHOW ALL C special obj	Size ON STEAM ON STEA	I LINE No In. No IRY COCKS No. Width ING ON 8	ED APPUI	CAPACITY Lb/I ON RETURN LINI ON RETURN LINI ON YES ON ANCES BLOW OFF PIPE Size in. Height FORM. Give of	in. Loo	E DRIVE Steam cation in. SEC	B CONNECTIONS CTIONS CTIONS CH) for	fm tu/Hr ons No	OUTLETS NO. STEAM I Yes INSPECTIO Yes DOES WE DOES ALI	CHE VAL'	Size PROPERLY D NO 111 "No ECK VES ENINGS COM G ON STEAL O (11 "No" 4 TERIAL OTH	PRAINED * explain FEE	PROPER PROPER In an back of D LINE Yes On back of D, BLOWOF on back of AN AS INDI	LY DRAINED I No (11 - I Iaim) No orm) F AND OTHE orm) CATED ABOV	RETURN	N LINE NO NO NO NO NO NO NO NO NO	E	
1 1 2 2 2	7 8 9	No. STOP VALVES FEED PIPE Size WATER GAGE O NO. CAST IRON B Length SHOW ALL C special obj	Size ON STEAM ON STEA	I LINE No In. No IRY COCKS No. Width ING ON 8	ED APPUI	CAPACITY Lb/f ON RETURN LINI Yes ANCES BLOW OFF PIPE Size in. Height FORM. Give consults as Do	in. Loo	E DRIVE Steam sation in, No use sketchill vessel	B connections Moto Ctions Ch) for setc	fm tu/Hr ons No	OUTLETS NO. STEAM Yes INSPECTIO YES DOES WE YES DOES ALI	CHE VAL DN OPE L DIN NO L MAT	Size PROPERLY D NO 111 "No ECK VES ENINGS COM G ON STEAL O (11 "No" 4 TERIAL OTH	PRAINED * explain FEE	PROPER PROPER In an back of D LINE Yes On back of D, BLOWOF on back of AN AS INDI	LY DRAINED I No (11 - I Iaim) No orm) F AND OTHE orm) CATED ABOV	RETURN	ON DECK OF FORM) N LINE N ON NO NO NO NO NO NO NO NO	i E	
1 1 2 2 2	7 8 9	NO. STOP VALVES FEED PIPE Size WATER GAGE ON NO. CAST IRON B Length SHOW ALL C SPECIAL OD NAME AND TIT	SIZE ON STEAM ON STEA	INC. PRINCE ON TO WHO	ED APPLIO	CAPACITY Lb/f ON RETURN LINI Yes ANCES BLOW OFF PIPE Size in. Height FORM. Give consults as Do	in. Loo	E DRIVE Steam sation in, No use sketchill vessel	B CONNECTIONS CTIONS CTIONS CH) for	fm tu/Hr ons No	OUTLETS NO. STEAM I Yes INSPECTIO Yes DOES WE DOES ALI	CHE VAL DN OPE L DIN NO L MAT	Size PROPERLY D NO 111 "No ECK VES ENINGS COM G ON STEAL O (11 "No" 4 TERIAL OTH	PRAINED * explain FEE	PROPER PROPER In an back of D LINE Yes On back of D, BLOWOF on back of AN AS INDI	LY DRAINED I No (11 - I Iaim) No orm) F AND OTHE orm) CATED ABOV	RETURN	N LINE NO NO NO NO NO NO NO NO NO	E	

This form may be obtained from The National Board of Boiler and Pressure Vessel Inspectors, 1055 Crupper Ave., Col's., O. 43229

Rev.

NATIONAL BOARD INSPECTION CODE

	OTHER CONDITIONS A	ID REQUIREMENTS	
MATERIAL CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CONTRACTOR CO			
;			
,			
	CODE STA	MPING	
s.			
(Back)			

FORM NB-6 BOILER-FIRED PRESSURE VESSEL

REPORT OF INSPECTION

Standard Form for Jurisdictions Operating Under the ASME Code

_							
1	DATE INSPECTED CERT EXP DATE CERTIFICATE POSTED C	OWNER NO	JURISDICTION NUMBER		NAT'L BD. NO	. I OTHER	ю. □
_	THES UNO	1111		1111	1.1.1	1 1 1 1	1 1 1 1 1
	ОЖНЕЯ		NATURE OF BUSINESS		XIND C	F INSPECTION	CERTIFICATE
_	1 4 1 4 5 7 5 7 1 4 1 1 1 1 1 4 1 4 1 4 1 5 7 1	1.1.1.1.1			□ IN	r 🗆 ext	TYES THE
2	OWNER STREET ADDRESS		OWNERS CITY			STATE	ZIP
	NUMBER						
_	USERS NAME - OBJECT LOCATION		1 1 1 1 1 1 1			OBJECTIONA	TION - COUNTY
	USERS NAME - OBJECT LOCATION		SPECIFIC LOCATION IN	PLANI		OBJECT COCA	non / coon i i
3				1111	1_1_1_		
_	USERS STREET ADDRESS		USERS CITY			STATE	ZIP
				1111	1 1 1	1 1 1	1111
	TYPE	YEAR BUIL	T MANUFACTURER				
4	D FT D WT D CI D OTHER						
_	USE		 	OD OF FIRING		PRESSURE GA	GF TESTED
5	□ POWER □ PROCESS □ STEAM HTG. □ HWH □ HWS □ OTHE						NO NO
_					T		
6	i i	AFETY-RELIEF VALVE			HEATING S	URFACE OR BIL	ı
_		ET AT	TOTAL CAPACITY		<u> </u>		
7	IS CONDITION OF OBJECT SUCH THAT A CERTIFICATE MAY BE ISSUE	ED?		HYDRO TEST			
_	YES ON OUT NO EXPLAIN FULLY UNDER CONDITIONS			☐ YES	PSI	DATE	no
_	CONDITIONS: With respect to the internal surface, describe and st	tale location of any sci	sie, oil or other deposits. Give to	cation and extent of	eny corresion a	nd state whethe	active
В	or inactive. State location and extent of any erosion.	grooving, buiging, wi	rping, cracking or similar condi	tion. Report on any o	delective livels.	Dowed, loase of	Droken
-	stays. State condition of all tubes, tube ends, coils cocks, safety valves, etc. Report condition of setting	s, nipples, etc. Descri in liginas ballles sui	be any adverse conditions with poorts, etc. Describe any major	respect to pressure changes or repairs :	gage, water co made since last	iumn, gage gias. Iinspection	i, gage
		· · · · · · · · · · · · · · · · · · ·					
							····
			· ·				
_							
			*				
_	· · · · · · · · · · · · · · · · · · ·	*********					*****
-					,		
	•						
_							
						*	
9	REQUIREMENTS: (List Code violations)						
_							
		· · · · · · · · · · · · · · · · · · ·					
	·						
_			··········			-	
	•						
10	NAME AND TITLE OF PERSON TO WHOM REQUIREMENTS WERE EXP	AINED					
	THE STATE OF PERSON TO WHOM REGULARMENTS WERE EXP	J					•
_	LUCOCOV CONTENT THE IS A TOP OF THE ISSUE OF						
	I HEREBY CERTIFY THIS IS A TRUE REPORT OF MY INSPECTION						
							IDENT NO
	SIGNATURE OF INSPECTOR	IDENT. NO	EMPLOYED BY				יייייייייייייייייייייייייייייייייייייי
		1111					
							N8-6

FORM NB-7 PRESSURE VESSELS

REPORT OF INSPECTION

Standard Form for Jurisdictions Operating Under the ASME Code

Γ.		OWNER NO)	JURISDICTION NUMBER	1	NAT'L BD. NO	. O OTHER	но. 🛘
Ľ	YES NO		L_L_			111		
	Ranwo			NATURE OF BUSINESS		KIND	OF INSPECTION	CERTIFICATE
2	OWNER STREET ADDRESS			OWNERS CITY		NI C		TYES H
	NUMBER			OWNERS CITY			STATE	ZIP
-	USERS NAME - OBJECT LOCATION			SPECIFIC LOCATION IN	I I I I I		OBJECT LOCA	TION - COUNTY
				or control cookinote life			0.000	
3	USERS STREET ADDRESS			USERS CITY			STATE	ZIP 1 1 1
1	NUMBER	1 1 1	1.1			1 1 1		1 1 1 1
4	TYPE		YEAR BUIL	T MANUFACTURER			*	
Ľ	AIR TANK WATER TANK OTHER	<u>l</u>			1 1 1 1			
5	USE			SIZE			PRESSURE GA	GE TESTED
-	STORAGE PROCESS HEAT EXCHANGE OTHER PRESSURE ALLOWED	SAFETY-RE	LIFE VALVE	<u> </u>		EVEL AIN IS	PRESSURE CH	NGED
6		SET AT	ac racre	TOTAL CAPACITY		EXPLAIN II	rheadone on	ANGEO
	IS CONDITION OF OBJECT SUCH THAT A CERTIFICATE MAY BE ISSU				HYDRO TEST	_1		
Ľ	YES ONO (IF NO EXPLAIN FULLY UNDER CONDITIONS)				TYES	PSI	DATE	по
8	CONDITIONS: With respect to the internal surface, describe and s	state locatio	n of any sca	ile, ail or other deposits. Give loc	ation and extent of	any corrosion	nd state whethe	zctive
L	or inactive. State location and extent of any erosion stays. State condition of all tubes, tube ends, con	ils, nipples,	etc. Describ	e any adverse conditions with i	espect to pressure	gage, water co	iumn, cage glas.	broken I, gage
	cocks, safety valves, etc. Report condition of setti	ing, linings,	ballies, sup	oports, etc. Describe any major (changes or repairs n	nade since las	i inspection.	
_								
_						~~····································		

-			·					
					·			
_	REQUIREMENTS: (List Gade violations)							
9	neutrinementa: (List Gode Woletlons)							
_								
	•							

-					,			
								
10	NAME AND TITLE OF PERSON TO WHOM REQUIREMENTS WERE EX	PLAINED:						
			~~~~		<del></del>			
	I HEREBY CERTIFY THIS IS A TRUE REPORT OF MY INSPECTION							
	SIGNATURE OF INSPECTOR	IDENT.	NO T	EMPLOYED BY			1	IDENT. NO
								1 1 1 1



## NATIONAL BOARD INSPECTION CODE

# PRESSURE VESSEL - REPORT OF INSPECTION - (EXTENSION SHEET)

DA	TE OF INSPECTION	OWNER-US	ER					LOCATION			
OWNER'S NO.	JURISDICTION NUMBER	N.B. ASME OR STD. NO.	INT.	EXT.	CERT.— NO. OF YEARS	TYPE OF OBJECT	YEAR BUILT	MADE BY	ALLOW. PRESS.	TEMP. OF	R.V.S.V. SETTING
		·									
											_
									<b>*</b>		
						·					
										-	
								:			

^{*}In this column show the number of years for which the Inspector authorizes the Issuance of the certificate.